Cascata Rain Barrel Instruction and Care Manual

Please read through all instructions before starting.

The Cascata is an excellent way to conserve water. The water kept in the Cascata Rain Barrel is for gardening purposes only and should not be consumed by humans or animals.

TO START

To install your Cascata Rain Barrel, you will need a down spout and a Flat Head Screw Driver. Everything else needed for installation is included with your Cascata.

Start by choosing a location for the Cascata Rain Barrel where there is a down spout nearby.

- 1. Place the Screen Guard in the open area on the top of the Cascata Rain Barrel.
- 2. Attach the Hook for the Hose to the Cascata Rain Barrel by placing it onto the ledge with the dimple, under the crown planter.
- 3. Attach the Nozzle with Shut-off Valve to the threaded end of the hose.
- 4. Attach the cut end of the Hose to the base of the Cascata Rain Barrel: Place the clamp over the hose, then insert hose over elbow connector. Use a Flat Head Screwdriver to tighten the clamp over the hose and the elbow connector. Then screw the threaded end of the elbow connector into the hole at the base of the Cascata.
- 5. Attach the tap to the body of the rain barrel. To prevent leakage, apply teflon tape to the tap's threads. Screw the tap in until it is tightened- do not over-tighten the tap.

USING THE PLANTER

The Cascata Rain Barrel was designed to fill a watering can. Purchase the Algreen pump kit upgrade to water directly from the rain barrel. To use the Cascata's crown planter, simply drill holes inside the planter. Fill the planter with soil and place plants inside.


CARE AND MAINTANCE

The Cascata Rain Barrel needs little care. The unique design of the Cascata Rain Barrel allows it to withstand extreme weather. During the winter months, drain the water inside the Cascata Rain Barrel by leaving the spigot and green nozzle open.


WARRANTY

The Cascata Rain Barrel carries a 20 Year Limited Warranty on the Barrel only. All accessories included in with the Cascata Rain Barrel are NOT included in the Warranty. The Warranty covers manufacturers' defects only. This Warranty does NOT cover neglect or owner's misuse.

Valid proof of purchase must be presented to make a warranty claim.




 Attach the other end of the hose to the base of the Cascata using a clamp. Use a flat head screwdriver to tighten clamp.
Screw the elbow connector into the hole on the bottom of the Cascata.





To divert water away from your foundation, clamp a length of 1.5" tubing to an overflow valve (tubing and clamp not included). The extra overflow is to accomodate the pump and linking upgrade kits. Purchase the Algreen pump kit to water directly from the rain barrel.

1. Non Corrosive Screen Gaurd goes into the open area.



3. Attach the Nozzle with Shut-off Valve to one end of the Hose.



100 Pinebush Road Cambridge Ontario Canada N1R 8J8 1-800-984-9933